borg& overström



Unrivalled performance

Solidly practical and visually striking, this innovative range brings a high capacity refreshment solution to any Horeca environment.







Dimensions Undercounter Twin Head Tap Dispense Height WxDxH 270x240x400mm 220x250x350mm 250mm

Max power consumption
Chilled & Sparkling 405W
Chilled & Ambient 365W

Dimensions Undercounter Triple Head Tap Dispense Height WxDxH 262x450x485mm 220x250x470mm 285mm

Max power consumption Chilled, Ambient & Sparkling 405W Power requirements
Hertz 50/Volts 240
Chilled Temperature
Min 2°C /Max 8°C
Throughput litres per hour
Chilled 30/60

- Key Features

 Robust, solid build quality

 Simple to operate and maintain

 Aesthetically striking

 Compact undercounter unit

 High capacity output

 Install Kit with filter included

 Available in chilled, ambient and sparkling

Available accessories

- Sanitisation Kit
- Sparkling Refill (CO₂E290) (600g) CO₂ Regulator with Gauge Large Driptray Blue Tint Cups (7oz)



Water options







Chilled

Ambient

Sparkling

Configuration



Undercounter

Recommended environment





Hospitality



Number of users





11 - 25

2

u2 Models

Direct Chill, Complete Undercounter System, Chilled & Ambient - 601350
Direct Chill, Complete Undercounter System, Chilled & Sparkling - 601380
Direct Chill, Complete Undercounter System, Chilled, Ambient & Sparkling - 601390

Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone +44 (0) 1362 695 006 Email sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838145 Version: 13012015