

borg&
overström



Beautifully
refreshing.

b2

borg& overström

A reliable classic

The appeal of the B2 lies in its outstanding reliability and uncomplicated design. Enjoy straightforward refreshment with no fuss.

Reasons to choose

- Simple to use and easy to maintain
- Robust build construction
- Available in direct chill or reservoir system
- Bottle conversion kit available

borgandoverstrom.com



Beautifully
refreshing.

b2

Water systems



Reservoir



Direct Chill



Countertop



Floorstanding

Water options



Chilled



Ambient



1-5



6-10



Hot



11-25

Available colours



Black



White



Silver



Beautifully
refreshing.

Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



Ultra-violet sterilising system
For added hygiene confidence, appliances can be fitted with Viovand™ – an ultra-violet sterilisation process that reduces water-born bacteria, available on direct chill machines only.



Laboratory certified 99.999% bacteria-free
Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen™.



Biofilm, limescale and impact resistant epoxy resin panel finish
Providing an increased level of hygiene and longevity, Fynil™ is a scratch and impact resistant epoxy-resin surface finish - effectively resisting biofilm development and limescale cohesion.

Sterizen is a registered trademark

Fynil is a registered trademark

Beautifully
refreshing.

B2 Models	Silver	White	Black
Reservoir, Countertop			
Chilled, Ambient	105110	105111	105112
Chilled, Hot	106110	106111	106112
Reservoir, Floorstanding			
Chilled, Ambient	105810	105811	105812
Chilled, Hot	106810	106811	106812
Direct Chill, Countertop			
Chilled, Ambient	107110	107111	107112
Direct Chill, Floorstanding			
Chilled, Ambient	107810	107811	107812
Chilled, Hot	107610	107611	107612

Power requirements

Hertz 50/Volts 220-240

Max power consumption

Chilled & Ambient 100W

Chilled & Hot 545W

Chilled temperature

Chilled & Ambient Min 4°C/Max 11°C

Direct Chill Min 2°C/Max 11°C

Hot temperature

Max 90°C

Throughput litres per hour

Chilled 25/Hot 6

Dimensions

Floorstanding

WxDxH

325x380x1060mm

Countertop

325x380x475mm

Dispense height

185mm



Beautifully
refreshing.



Talk to an adviser:

01892 669609

sales@divinewater.co.uk

www.divinewater.co.uk