



AquaCafé®

Bottled Water or
Filtration Cooler
for Capsules

Divine
EST 1994 WATER
BOTTLED & MAINS-FED WATER DISPENSERS



Features

- Single-serve coffee & tea in about 45 seconds, and hot & chilled water for residential and small offices
- Hotter water for barista quality coffee, tea and for cooking instant noodles and soups
- Space saver – frees up counter space, no brewer or coffee pot on the counter or filtration system at the sink
- Time saver – Barista quality coffee brewed at home. No drive to expensive coffee shop or waiting in line
- Brews 6 oz, 8 oz, 10 oz, 12 oz and 14 oz cup sizes
- Safety lock function for hot water
- Easy-to-use touch screen with illuminated dispensing area and brightness controls
- Adjustable drip tray that's removable for easy cleaning
- 1L / .26G stainless steel hot tank
- 3.78L / 1G cold tank
- Bottle water models load from the bottom so there is no lifting of heavy bottles – they slide in place
- Filtration models have room inside for most filters (filter supplied may differ from picture above).
- Sealed controls keep out dirt and liquid
- **Accu-Temp®** – Serves water at the proper temperature every time
- **Stay-Cool®** — Keeps residual water in the cold waterway chilled and ready to serve

Call Divine Water Now for more information on 03300 241 870 or see our website

www.divinewater.co.uk

Divine
EST 1994 WATER
BOTTLED & MAINS-FED WATER DISPENSERS

Power

Voltage (V)	220 V
Frequency (Hz)	50
Total Power Consumption	1300W
Cold Power Consumption	100W
Hot Power Consumption	1200W

Brewer Hot Water System

Avg. Hot Water Temp at Nozzle @ 75°F ambient (Cut-in / Cut-out)	194 / 201.2°F
Hot Thermostat / Heat Limiter	221°F
Hot Thermostat / Therimstor Cycle	194-201.2°F
Hot Tank Size (Liter : Gallon)	1L : .26G
Heating Element	Internal Heating Element

Hot Water System

Avg. Hot Water Temp at Nozzle @77°F Ambient	Cup 1	Cup 2	Cup 3
Cut-in Temp:	174.38°F (79.1°C)	175.1°F (79.5°C)	174.74°F (79.3°C)
Cut-out Temp:	194.9°F (90.5°C)	195.26°F (90.7°C)	193.64°F (89.8°C)
Hot Water ARI Rating	121, 6 oz (178ml) >165°F (74°C) +/-10%		
Hot Thermometer / Heat Limiter	221°C		
Hot Thermostat / Thermistor Cycle	Cut-in: 72.4°F (78°C) Cut-out: 190.4°F (88°C)		
Hot Water Flow Rate	0.49 oz/sec (13.92 ml/sec)		
Heating Element	Internal Heating Element		

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient	Cup 1	Cup 2	Cup 3
Cut-in Temp:	45.7°F (7.6°C)	45.14°F (7.3°C)	46.4°F (8°C)
Cut-out Temp:	43.88°F (6.6°C)	42.44°F (5.8°C)	42.98°F (6.1°C)
Cold Water ARI Rating	18, 5 oz (147ml) < 50°F (10°C) +/- 10		
Cold Thermostat Set Point	Cut-in: 50F (10° C) Cut-Out: 45°F (7°C)		
Cold Water Flow Rate	1.073 oz/sec (30.42 ml/sec)		
Cold Tank Size / Usable Volume (Liter : Gallon)	3.8 / 2.8 : 1 / 0.74		

Weights and Measurements

Net Weight : Gross Weight (Lbs)	37.48 : 43.4
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	17.04 x 14.09 x 43.5 / 17.52 x 14.76 x 45.67
Container Load (20') : (40')	160 : 334
Container Load (40' HC) : (45' HC)	334 : 372
Max Distance from Drip Try to Faucet (Adjustable) (Inch : mm)	8.75 : 222.25
Faucet / Dispense Height (Inch : mm)	37.5 : 952.5

Certifications and Listings

Energy Star	UL
-------------	----

Filter Compartment Dimensions

Width (Inch : mm)	12 : 304.79
Depth (Inch : mm)	11 : 279.4



Official Keurig Pods & Accessories

Pods



Italian Roast
Coffee



Italian Roast
Decaf Coffee



Twinings English
Breakfast Tea



Café Escapes
Hot Chocolate

Accessories



Red Bean 12oz
Paper Cups



12oz Red Bean
Sip Thru Lid



Keurig Branded
10oz Paper Cups



Keurig Branded
10oz Cup Lids



140mm Wooden
Stirrers



Squash STIX in Orange
or Apple & Blackcurrant



5 Column Cup & Lid Holder



Keurig Pod Display Unit



Keurig Pod Display Carousel